



19/17/15 inch water-proof CA/IR/SAW touchscreen  
 Motorized card reader  
 Metal EPP  
 Receipt printer  
 Invoice printer  
 Bill validator  
 High performance host computer  
 UPS  
 Stereo audio



Component/function layouts

Applications

- Telecom self service payment
- Invoice printing kiosk
- Debit card payment
- Credit card payment
- Utility bill collection
- Information ads

Features

1. Powerful up-to-date CPU;
2. Waterproof IR/SAW touchscreen;
3. CASHCODE universal cash acceptor;
4. DES EPP with motorized card reader;
5. Invoice dot-matrix printer;
6. Bank passbook printer and list printer
7. All steel sleek anti graffiti enclosure

Specifications

Model Name	A8E-17EL	A8M-19NE
Processor	2.5GHz Intel® Core™ i3 2100T	3.0GHz Intel® Pentium™ E6600(fan)
RAM	4Gb DDR II(16G max)	2Gb DDR II(4G max)
HDD	64G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Monitor	17" LCD with DX9 decoding acceleration	19" LCD with DX9 decoding acceleration
Touchscreen	Water proof CA/IR/SAW touchscreen	
Receipt printer	CUSTOM TG2480	CUSTOM TG2480
Invoice printer	STAR DP912	
Metal EPP	MKP2920	
Cashcode cash acceptor	CASHCODE SM	CASHCODE SM
List printer	(Optional)	(Optional)
Motorized card reader	Rm6 hybrid card reader for IC, Magnetic and M1 cards	
3G/GPRS Modem(optional)	Simemse MC55/52 GPRS dual band SMS modem	
UPS	SANTAK K1000 PRO UPS for at least 15 mins of power	
Audio	Bi-stereo channel 2X3W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 45-56cm * 45-66cm * 145-165cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6/3.1, Ubuntu, Fedora	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

