

Touchscreen digital signage

Digital Signage

D1

Applications

Museum
Exhibition
Apps store
Presentation
Information kiosk

Features

1. Dual Core Intel Core i3 2100;
2. Full HD touchscreen monitor;
3. Full view angle IPS display;
4. Multi touch support
5. All steel anti-graffiti enclosure

Component/function layouts



42" FULL HD touchable IPS main monitor



All steel anti-graffiti enclosure stand

Specifications



Part Name	D1A-42EE	D1E-46RC
Processor	Intel Core i3 2100	Intel Core G2020
RAM	4Gb DDR III(16G max)	4Gb DDR III(16G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Display	42" LCD display with LED backlight	46" LCD display with LED backlight
Touchscreen	42" waterproof IR touchscreen	46" waterproof IR touchscreen
RFID	None	720pixel HD PINHOLE camera
Rear I/O Connectors	Power Jack Fuse(3A) Power switch Host computer Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	WINDOWS XP/7/Linux 2.6 distribution(i.e. Fedora 9, CentOS 5, Ubuntu 10 and SUSE etc)	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

