

Touchscreen digital signage

Digital Signage D11

Applications

Museum
Exhibition
Apps store
Presentation
Information kiosk

Features

1. Dual Core Intel Core i3 2100;
2. Full HD touchscreen monitor;
3. Full view angle IPS display;
4. Multi touch optional
5. All steel anti-graffiti enclosure

Component/function layouts



External antenna

HD Camera

46/55/65" FULL HD touchable IPS main monitor

All steel anti-graffiti enclosure stand



Specifications

Part Name	D11A-46DIDT	D11A-55RFC
Processor	Intel Pentium G3420T	Intel Core i5 4770T
RAM	4Gb DDR III(16G max)	4Gb DDR III(16G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Display	46" LCD display	55" LCD display with DID LED backlight
Touchscreen	46" waterproof IR touchscreen	55" waterproof IR touchscreen
WIFI(optional)	Intel Integrated miniPCIe WIFI with external antenna	
HD Camera(optional)	Logitech C310	
Rear I/O Connectors	Power Jack Fuse(3A) Power switch Host computer Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	WINDOWS XP/7/Linux 2.6 distribution(i.e. Fedora 9, CentOS 5, Ubuntu 10 and SUSE etc)	
Operating Temperature	0°C up to 50°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

CE FC

