

Wallmount Kiosk J11

Applications

- Internet browse
- Exhibition demonstration
- Information ads

Features

1. Industrial mini-ITX motherboard;
2. Waterproof IR/SAW touchscreen;
3. Thermal printer
4. 2D barcode reader
5. All steel sleek enclosure



- Light box(LED)
- Camera(5MP)
- 19/17/15 inch water-proof touchscreen
- 2D barcode scanner
- High performance thermal printer
- Industrial host computer
- RFID reader
- Stereo audio



Component/function layouts

Specifications

Model Name	J11A-17NV80F	J11B-19NK403F
Processor	1.8 G Intel i3/i5 CPU	Intel® Core™Celeron 1037 CPU(fan)
RAM	4Gb DDR 3(16G max)	8Gb DDR III(max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Monitor	17" LCD with DX9 decoding acceleration	19" LCD with DX9 decoding acceleration
Touchscreen	Water proof Capacitive/IR/SAW touchscreen	
NFC(optional)	RFID/contactless card reader	
Thermal printer	CUSTOM TG2480	ZEBRA KR403
Barcode reader	Honeywell HF5180/5680 2D barcode reader engine	
Camera	Logitech C310 5MP camera	
Audio	Bi-stereo channel 2X10W speakers	
Enclosure	Durable all SPCC steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 45cm * 52cm * 163cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6, Ubuntu9, Fedora10	
Operating Temperature	0°C up to 50°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

