

Payment Kiosk with thermal/dotmatrix printer and barcode reader



Applications

- Payment accepting
- Invoice giving
- Ticketing vending
- Barcode coupon selling

Features

1. Waterproof SAW touchscreen;
2. Lockable Metallic keyboard with laser trackball(optional)
3. A4 laser printer
4. Mobile on Desktop(MoDT) industrial computer
5. Rugged VoIP phone
6. POS terminal adds-on
7. All steel anti graffiti enclosure
8. Integrated light box



Thermal/Dotmatrix printer
Laser barcode scanner

UPS(internal)
Mobile on Desktop(MoDT) IPC

Low noise fans with replaceable foam



3G/GPRS SMS Antenna
LOGO&Light box
PIN hole camera
Dual stereo audio
15/17/19 inch water-proof touchscreen

Motorised card reader/Cash acceptor
Metal PIN pad



Component/function layouts

Specifications

Model Name	T5B-17HU	T5B-17C
Processor	Intel® Core™ 2 DUO 7200(fan)	Intel® Core™ 2 i3 2100(fan)
Chipset	Intel® GM45	Intel® B75M
RAM	2Gb DDR II(max)	4Gb DDR III(max)
HDD	320G 7200rpm 3.5" hard driver Up to 3TB size	Intel 330 series 80G 2.5" SSD(MLC) Up to 3TB size
Monitor	17" LCD with DX9 decoding acceleration	17" LCD with DX9 decoding acceleration
Touchscreen	Water proof SAW touchscreen with function keys	
Light Box	Acrylic cover with light tube inside	
Receipt/Ticket printer	CUSTOM®(Italy brand) TG2480	STAR 912 9 pin dot-matrix printer
Cash validation(option)	MEI@ SCL83 cash validator	(None)
Motorised card reader	SANKYO ICT3K7 hybrid card reader	
Photo or A4 laser printer	(Optional)	SAMSUNG ML2165 laser printer
Telephone&POS(Add-on)	Rugged VoIP phone(Optional)	POS NEWPOS8112(Optional)
EPP metal keypad	MKP2920SEA 3DES EPP(optional)	MKP2920SEA 3DES EPP(optional)
Barcode reader	HONEYWELL® 4823F 1D Laser Reader	(None)
GPRS Modem	Simense MC55 GPRS dual band SMS modem	
UPS	SANTAK K500 PRO UPS for at least 5 mins of power	
Audio	Bi-stereo channel 2X15W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: (package)680*750*2030mm; (machine)590x650x1730/1850mm	
Rear I/O Connectors	Power Jack Fuse(5A) Power switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 5A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6, Ubuntu9, Fedora10	
Operating Temperature	0°C up to 50°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

